

S6-GC3P(25-40)K03-ND

Solis Three Phase Grid-Tied Inverters

Features:

- Max. efficiency 98.6%
- String current up to 20A
- > 150% DC/AC ratio, supports high power modules
- Automatic voltage stabilization technology in weak grid conditions
- AFCI protection, proactively reduces fire risk
- Supports RS485/ WiFi/GPRS/4G
- Scrolling information display, making it easier to monitor inverter operation
- Scan to register on SolisCloud, supports remote upgrade and control

Models:

S6-GC3P25K03-NV-ND
S6-GC3P30K03-NV-ND
S6-GC3P33K03-NV-ND
S6-GC3P36K03-NV-ND
S6-GC3P40K03-HV-ND



DATASHEET

S6-GR3P(25-40)K03-ND

Models	25K03-NV	30K03-NV	33K03-NV	36K03-NV	40K03-HV
Input DC					
Recommended max. PV power	37.5 kW	45 kW	49.5 kW	54 kW	60 kW
Max. input voltage			1100 V		
Rated voltage		600 V			720V
Start-up voltage		180 V			
MPPT voltage range		180-1000 V			
Max. input current		40 A / 40 A / 40 A			
Max. short circuit current		50 A / 50 A / 50 A			
MPPT number/Max. input strings number		3/6			
Output AC					
Rated output power	25 kW	30 kW	33 kW	36 kW	40 kW
Max. apparent output power	27.5 kVA	33 kVA	36.3 kVA	39.6 kVA	44 kVA
Max. output power	27.5 kW	33 kW	36.3 kW	39.6 kW	44 kW
Rated grid voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V			3/PE, 480 V
Rated grid frequency		50 Hz / 60 Hz			
Rated grid output current	38.0 A / 36.1 A	45.6 A / 43.3 A	50.1 A / 47.6 A	54.7 A / 52 A	48.1 A
Max. output current	41.8 A	50.2 A	55.1 A	60.2 A	53 A
Power factor		>0.99 (0.8 leading - 0.8 lagging)			
THDi		<3%			
Efficiency					
Max. efficiency		98.5%			98.6%
EU efficiency		98%			98.1%
Protection					
DC reverse-polarity protection			Yes		
Short circuit protection			Yes		
Output over current protection			Yes		
Surge protection			DC Type II / AC Type II		
Grid monitoring			Yes		
Anti-islanding protection			Yes		
Temperature protection			Yes		
Strings monitoring			Yes		
I/V Curve scanning			Yes		
Integrated AFCI (DC arc-fault circuit protection)			Yes ⁽¹⁾		
Integrated DC switch			Yes		
General Data					
Dimensions (W*H*D)			355*625*250 mm		
Weight			26.8 kg		
Topology			Transformerless		
Self-consumption (night)			<1 W		
Operating ambient temperature range			-25 ~ +60°C		
Relative humidity			0-100%		
Ingress protection			IP66		
Cooling concept			Intelligent redundant fan-cooling		
Max. operation altitude			4000 m		
Grid connection standard		G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530			
Safety/EMC standard			IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4		
Features					
DC connection			MC4 connector		
AC connection			OT terminal		
Display			LED, Bluetooth + APP		
Communication			RS485, Optional: Wi-Fi, GPRS		

(1) Activation required.