

## S6-GU(250-350)K-EHV-US

# Solis Three Phase Grid-Tied Inverters

### Efficient

- 12/16 MPPTs, max. efficiency 99.0%
- > 150% DC/AC ratio
- Lower starting voltage, longer power generation time
- Wide MPPT current design, compatible with 182 and 210 series bifacial modules

### Smart

- Night SVG function
- Intelligent string monitoring, Smart I-V curve scan
- Remote firmware upgrade with simple operation

### Safe

- Type 4X, C5 Anti-Corrosion Level
- Built-in PID recovery for better module performance
- Fuse free design, safe and maintenance free

### Economic

- Power line communication (PLC) (optional)
- Integrated tracking bracket power supply interface

### Models:

S6-GU250K-EHV-US-M12  
S6-GU300K-EHV-US-M12  
S6-GU350K-EHV-US-M12  
S6-GU350K-EHV-US-M16



## DATASHEET

## S6-GU(250-350)K-EHV-US

Models	250K-M12	300K-M12	350K-M12	350K-M16
<b>Input DC</b>				
Max. input voltage			1500 V	
Rated voltage			1080 V	
Start-up voltage			500 V	
MPPT voltage range			480-1500 V	
Max. input current		12*40 A		16*30 A
Max. short circuit current		12*70 A		16*60 A
MPPT number/Max. input strings number		12/12		16/16
<b>Output AC</b>				
Rated output power	250 kW	300 kW	350 kW	
Max. apparent output power	250 kVA	300 kVA	350 kVA	
Max. output power	250 kW	300 kW	350 kW	
Rated grid voltage	3Φ/PE, 600 V	Φ/PE, 690 V	3Φ/PE, 800 V	
Rated grid frequency			60 Hz	
Max. output current	240.6 A	251.0 A	252.6 A	
Power factor		>0.99 (0.8 leading - 0.8 lagging)		
THDi			<3%	
<b>Efficiency</b>				
Max. efficiency		99.0%		
CEC efficiency		98.5%		
<b>Protection</b>				
DC reverse-polarity protection		Yes		
Anti-islanding protection		Yes		
Strings monitoring		Yes		
I/V Curve scanning		Yes		
Integrated AFCI (DC arc-fault circuit protection)		Yes		
Integrated PID recovery		Yes		
<b>General Data</b>				
Dimensions (W*H*D)		45.9*37.2*16.3 in (1227*995.8*463.8 mm)		
Weight		297 lbs (135 kgs)		
Topology		Transformerless		
Self-consumption (night)		<3 W		
Operating ambient temperature range		-22°F to 140°F (-30°C to +60°C)		
Relative humidity		-40°F to 176°F (-40°C to 80°C)		
Ingress protection		TYPE 4X		
Cooling concept		Intelligent redundant fan-cooling		
Max. operation altitude		13,120 ft (4000 m)		
Compliance		UL 1741, UL 1998, UL 1699B, IEEE 1547, FCC Part 15 (Class A & B), CAN/CSA C22.2 107.1-1, California Rule 21 Phases II & III		
<b>Features</b>				
DC connection		MC4 connector		
AC connection		OT terminal (1000 MCM)		
Display		LED, Bluetooth + APP		
Communication		RS485, Optional: PLC		