



Product Service

# CERTIFICATE

No. B 086470 0093 Rev. 04

**Holder of Certificate:** **Ginlong Technologies Co., Ltd.**

No.57 Jintong Road  
Binhai Industrial Park, Xiangshan  
315712 Ningbo, Zhejiang  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**



**Product:**

**Converter  
Off-grid inverter**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704092008131-04

**Valid until:** 2029-04-17

**Date,** 2024-04-24

( Zhengdong Ma )

# CERTIFICATE

No. B 086470 0093 Rev. 04

Model(s):

S5-EO1P4K-48, S5-EO1P4K-48-P, S5-EO1P5K-48,  
S5-EO1P5K-48-P, S6-EO1P4K-48, S6-EO1P5K-48  
S6-EO1P4K-48-EU, S6-EO1P5K-48-EU, S6-EO1P4K-L,  
S6-EO1P5K-L

## Parameters:

Model	S5-EO1P4K-48, S5-EO1P4K-48-P	S5-EO1P5K-48, S5-EO1P5K-48-P
PV Input		
Max. Input Voltage d.c.	d.c. 500 V	
MPPT Voltage range Voltage d.c.	d.c. 90 V ... 480 V	
Max. input Current d.c.	d.c. 13 A/13 A	
Isc PV (absolute max.) d.c.	d.c. 32 A	
Battery		
Battery Voltage Range d.c.	d.c. 40V ... 60 V	
Max. Charge Current d.c.	d.c. 100 A	
Max. Discharge Current d.c.	d.c. 100 A	
AC-Output (stand-alone)		
Max. Output Power	4 kVA/4 kW	5 kVA/5 kW
Nominal Output Voltage a.c.	1/N/PE AC 230V	
Output Frequency a.c.	50/60 Hz	
Max. Output Current a.c.	a.c. 20 A	a.c. 25 A
AC-Input		
Nominal Input Voltage a.c.	1/N/PE AC 230 V	
Max. Input Continuous Current a.c.	a.c. 26 A	a.c. 30 A
Input Frequency a.c.	50/60 Hz	
Others		
Protective Class	Class I	
Ingress Protection	IP 21	
Overvoltage Category	III (AC), II(DC)	
Operation Temperature Range	-10 °C...60 °C	

# CERTIFICATE

No. B 086470 0093 Rev. 04

Model	S6-EO1P4K-48 S6-EO1P4K-48-EU	S6-EO1P5K-48 S6-EO1P5K-48-EU
PV Input		
Max. Input Voltage d.c.	d.c. 500 V	
MPPT Voltage range Voltage d.c.	d.c. 90V ... 430 V	
Max. input Current d.c.	d.c. 16 A/16 A	
Isc PV (absolute max.) d.c.	d.c. 40 A	
Battery		
Battery Voltage Range d.c.	d.c. 40V ... 60 V	
Max. Charge Current d.c.	d.c. 100 A	
Max. Discharge Current d.c.	d.c. 100 A	
AC-Output (stand-alone)		
Max. Output Power	4 kVA/4 kW	5 kVA/5 kW
Nominal Output Voltage a.c.	1/N/PE AC 230 V	
Output Frequency a.c.	50/60 Hz	
Max. Output Current a.c.	a.c. 20 A	a.c. 25 A
AC-Input(For grid port and Gen port)		
Nominal Input Voltage a.c.	1/N/PE AC 230 V	
Max. Input Continuous Current a.c.	a.c. 26 A	a.c. 30 A
Input Frequency a.c.	50/60 Hz	
Others		
Protective Class	Class I	
Ingress Protection	IP 21	
Over voltage Category	III (AC), II(DC)	
Operation Temperature Range	-10°C ...60°C	

# CERTIFICATE

No. B 086470 0093 Rev. 04

Model	S6-EO1P4K-L	S6-EO1P5K-L
PV Input		
Max. Input Voltage d.c.	d.c. 500 V	
MPPT Voltage range Voltage d.c.	d.c. 90V ... 430 V	
Max. input Current d.c.	d.c. 16 A/16 A	
Isc PV (absolute max.) d.c.	d.c. 40 A	
Battery		
Battery Voltage Range d.c.	d.c. 40V ... 60 V	
Max. Charge Current d.c.	d.c. 100 A	
Max. Discharge Current d.c.	d.c. 100 A	
AC-Output (stand-alone)		
Max. Output Power	4000W	5000W
Nominal Output Voltage a.c.	1/N/PE AC 220 V	
Output Frequency a.c.	60 Hz	
Max. Output Current a.c.	a.c. 20 A	a.c. 25 A
AC-Input(For grid port and Gen port)		
Nominal Input Voltage a.c.	1/N/PE AC 220 V	
Max. Input Continuous Current a.c.	a.c. 26 A	a.c. 30 A
Input Frequency a.c.	60 Hz	
Others		
Protective Class	Class I	
Ingress Protection	IP 21	
Over voltage Category	III (AC), II(DC)	
Operation Temperature Range	-10°C ...60°C	

**Tested according to:** EN 62109-1:2010  
IEC 62109-1:2010  
EN 62109-2:2011  
IEC 62109-2:2011