



Product Service

# Compliance Document

No. D 086470 0175 Rev. 01

**Holder of Certificate:** **Ginlong Technologies Co., Ltd.**  
No.57 Jintong Road  
Binhai Industrial Park, Xiangshan  
315712 Ningbo, Zhejiang  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Converter**  
**Hybrid Inverter**

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704092304886-01

**Date,** 2024-08-02

( Zhengdong Ma )



Product Service

# Compliance Document

No. D 086470 0175 Rev. 01

**Model(s):** S6-EH3P12K-H, S6-EH3P15K-H, S6-EH3P20K-H

**Parameters:**

Model	S6-EH3P12K-H	S6-EH3P15K-H	S6-EH3P20K-H
a).PV inputs:			
Max. input voltage	DC 1000 V		
MPP voltage range	DC 200, ..., 850 V		
Max. input current	DC 4x20 A	DC 4x20 A	DC 4x20 A
Isc PV (absolute maximum)	DC 4x30 A	DC 4x30 A	DC 4x30 A
b).Battery			
Battery type	Li-ion		
Battery voltage range	DC 120, ..., 800 V		
Max. charge/discharge current	DC 50/50 A	DC 50/50 A	DC 50/50 A
c).AC-output (Grid side)			
Rated output voltage	3/N/PE AC 230/400 V		
Rated output frequency	50 Hz		
Rated output current	AC 17.3 A	AC 21.7 A	AC 28.9 A
Max. /Rated apparent output power	12000 VA	15000 VA	20000 VA
Max. output current:	AC 17.3 A	AC 21.7 A	AC 28.9 A
Displacement factor:	-0.8, ..., 1, ..., +0.8		
d).AC-output (Back-up)			
Rated output voltage	3/N/PE AC 230/400 V		
Rated output frequency	50 Hz		
Rated output current	AC 17.3 A	AC 21.7 A	AC 28.9 A
Max. /Rated output power	12000 W	15000 W	20000 W
Max. output current:	AC 17.3 A	AC 21.7 A	AC 28.9 A
Displacement factor:	-0.8, ..., 1, ..., +0.8		
e).AC-Input			
Rated output voltage	3/N/PE AC 230/400 V		
Rated output frequency	50 Hz		
Max.(Rated) output current	AC 26 A	AC 32.5 A	AC 43.3 A

**Tested according to:** NRS 097-2-1:2024