

RHI-3P(5-10)K-HVES-5G

Solis Three Phase High Voltage Energy Storage Inverters

Features:

- Max. efficiency 98.4%
- 2 MPPT and 4 DC input; Max 26A DC input current
- 3 operating modes (self-consumption; time-of-use; off-grid back-up) & programmable energy management
- Power supply can be switched automatically and switching time within 40ms
- Ensures AC backup for up to 10kW of continuous power and 16kVA of peak power
- Time of use shifting and peak shaving capabilities to grid
- AFCI protection, proactively reduces fire risk
- Intelligent EMS function
- Support three-phase imbalance on backup output port
- 24-hour fully intelligent energy management, Real-time grasp of PV plant status
- Remotely control & upgrade function, making digital power plant maintenance at your fingertips

Models:

RHI-3P5K-HVES-5G / RHI-3P6K-HVES-5G

RHI-3P8K-HVES-5G / RHI-3P10K-HVES-5G



360° View

DATASHEET

RHI-3P(5-10)K-HVES-5G

Models	5K	6K	8K	10K
Input DC (PV side)				
Recommended max. PV power	8 kW	9.6 kW	12.8 kW	16 kW
Max. input voltage	1000 V			
Rated voltage	600 V			
Start-up voltage	160 V			
MPPT voltage range	200 - 850 V			
Max. input current	13 A / 13 A		26 A / 13 A	26 A / 26 A
Max. short circuit current	16.5 A / 16.5 A		32.5 A / 16.5 A	32.5 A / 32.5 A
MPPT number / Max. input strings number	2 / 2		2 / 3	2 / 4
Battery				
Battery type	Li-ion			
Battery voltage range	160 - 600 V			
Max. charge / discharge power	5 kW	6 kW	8 kW	10 kW
Max. charge / discharge current	25 A			
Communication	CAN			
Input AC (Grid side)				
Input voltage range	320 - 480 V			
Max. apparent input power	5 kVA	6 kVA	8 kVA	10 kVA
Max. input current	25 A			
Frequency range	45 - 55 Hz / 55 - 65 Hz			
Output AC (Grid side)				
Rated output power	5 kW	6 kW	8 kW	10 kW
Max. apparent output power	5.5 kVA	6.6 kVA	8.8 kVA	10 kVA
Operation phase	3/N/PE			
Rated grid voltage	380 V / 400 V			
Rated grid frequency	50 Hz / 60 Hz			
Rated grid output current	7.6 A / 7.3 A	9.2 A / 8.7 A	12.2 A / 11.6 A	15.2 A / 14.5 A
Max. output current	8.4 A	10 A	13.4 A	16.7 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)			
THDi	< 2%			
Output AC (Back-up)				
Rated output power	5 kW	6 kW	8 kW	10 kW
Peak apparent output power	10 kVA, 60 s	12 kVA, 60 s	16 kVA, 60 s	16 kVA, 60 s
Back-up switch time	< 40 ms			
Rated output voltage	3/N/PE, 380 V / 400 V			
Rated frequency	50 Hz / 60 Hz			
Rated output current	7.6 A / 7.3 A	9.2 A / 8.7 A	12.2 A / 11.6 A	15.2 A / 14.5 A
THDv (@linear load)				
Efficiency				
Max. efficiency	98.4%			
EU efficiency	97.7%			
MPPT efficiency	99.9%			
Battery charge / discharge efficiency	97.5%			
Protection				
Anti-islanding protection	Yes			
Output over current protection	Yes			
Short circuit protection	Yes			
Integrated AFCI	Yes ⁽¹⁾			
Integrated DC switch	Optional			
DC reverse-polarity protection	Yes			
PV over voltage protection	Yes			
Battery reverse protection	Yes			
General Data				
Dimensions (W*H*D)	535 × 455 × 185 mm			
Weight	25.1 kg			
Topology	Transformerless			
Standby consumption	< 15 W			
Operating ambient temperature range	-25 ~ +60°C			
Relative humidity	0 - 100%			
Ingress protection	IP65			
Cooling concept	Natural cooling			
Max. operation altitude	4000 m			
Grid connection standard	G98 or G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1, VDE 0126/UTE C 15/VFR:2019, RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA			
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-3			
Features				
DC connection	MC4 connector			
AC connection	Quick connection plug			
Display	LCD			
Communication	RS485, Optional: Wi-Fi, GPRS			

(1) Activation required.