

## S5-E01P(4-5)K-48

# Solis Single Phase Low Voltage Off-Grid Inverters

### Features:

- One-click fast charging mode
- Generator on and off will be added into system logic, more intelligent
- The newly added force-charging period can optimize the revenue according to the difference of electricity price
- Battery equalization for increased battery performance and lifespan

### Models:

S5-E01P4K-48 / S5-E01P4K-48-P

S5-E01P5K-48 / S5-E01P5K-48-P



360° View



## DATASHEET

## S5-E01P(4-5)K-48

Models	4K	4K-P	5K	5K-P
Parallel capability	No	Yes, 6 units	No	Yes, 6 units
<b>Battery</b>				
Rated battery voltage	48 V			
Battery type	Li-ion / Lead-acid			
Max. charge / discharge current	100 A			
Communication	CAN			
<b>Inverter Output</b>				
Rated output power	4 kVA / 4 kW		5 kVA / 5 kW	
Rated output voltage	230 V ± 1%			
Rated frequency	50 Hz / 60 Hz ± 0.1%			
Surge capacity	8 kVA		10 kVA	
Output voltage waveform	Pure sine wave			
Transfer time	10 ms typical, 20 ms Max			
THDv (@linear load)	<3%			
Peak efficiency (PV-AC)	96.6%			
<b>Solar Charger</b>				
Solar charger type	MPPT			
Recommended max. PV power	4.5 kW		5.5 kW	
Max. input voltage	500 V			
MPPT voltage range	90-480 V			
MPPT number/Max. input strings number	1/2			
Max. input current per MPPT	27 A			
Max. solar charge current	100 A			
<b>AC Charger</b>				
Rated input voltage	230 V			
Selectable voltage range	90-280 V			
AC frequency range	50 Hz / 60 Hz (Auto sensing)			
Max. AC charge current	60 A		80 A	
<b>Protection</b>				
Output over voltage protection	Yes			
Output over current protection	Yes			
Short circuit protection	Yes			
Surge protection	Yes			
Temperature protection	Yes			
Integrated AFCI (DC arc-fault circuit protection)	Yes <sup>(1)</sup>			
<b>General Data</b>				
Dimensions (W*H*D)	335*450*160 mm			
Weight	14 kg			
Relative humidity	5% - 95% (Non-condensing)			
Operating ambient temperature range	-10 ~ +60°C			
Storage temperature range	-25 ~ +60°C			
Ingress protection	IP21			
Max. operation altitude	2000 m			
Safety standard	IEC 62109, IEC 61000, 55011, RED			
<b>Features</b>				
DC connection	Terminal connectors			
AC connection	Terminal connectors			
Display	LCD			
Communication	CAN, BMS, Dry-contact, Bluetooth, Optional: Wi-Fi			

(1) Activation required.