

S5-GR3P(3-20)K

Solis Three Phase Grid-Tied Inverters

Efficient

- Max. efficiency 98.7%
- String current up to 16A
- Wide voltage range and low startup voltage

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Automatic voltage stabilization technology in weak grid conditions

Smart

- Supports export power control
- Supports RS485, WiFi, GPRS
- Scan to register on SolisCloud, supports remote upgrade and control

Economic

- Compact design, simple installation and maintenance
- > 150% DC/AC ratio
- Supports high power modules for lower installation costs

Models:

S5-GR3P3K / S5-GR3P4K

S5-GR3P5K / S5-GR3P6K

S5-GR3P8K / S5-GR3P9K

S5-GR3P10K / S5-GR3P12K

S5-GR3P13K / S5-GR3P15K

S5-GR3P17K / S5-GR3P20K



360° View

DATASHEET

S5-GR3P(3-20)K

Models	3K	4K	5K	6K	8K	9K	10K	12K	13K	15K	17K	20K	
Input DC													
Recommended max. PV power	4.5 kW	6 kW	7.5 kW	9 kW	12 kW	13.5 kW	15 kW	18 kW	19.5 kW	22.5 kW	25.5 kW	30 kW	
Max. input voltage								1100 V					
Rated voltage								600 V					
Start-up voltage								180 V					
MPPT voltage range								160 - 1000 V					
Max. input current					16 A / 16 A					32 A / 32 A			
Max. short circuit current					20 A / 20 A					40 A / 40 A			
MPPT number / Max. input strings number					2 / 2					2 / 4			
Output AC													
Rated output power	3 kW	4 kW	5 kW	6 kW	8 kW	9 kW	10 kW	12 kW	13 kW	15 kW	17 kW	20 kW	
Max. apparent output power	3.3 kVA	4.4 kVA	5.5 kVA	6.6 kVA	8.8 kVA	9.9 kVA	11 kVA	13.2 kVA	14.3 kVA	16.5 kVA	18.7 kVA	22 kVA	
Rated grid voltage								3/N/PE, 220 V / 380 V, 230 V / 400 V					
Rated grid frequency								50 Hz / 60 Hz					
Rated grid output current	4.6 A / 4.3 A	6.1 A / 5.8 A	7.6 A / 7.2 A	9.1 A / 8.7 A	12.2 A / 11.5 A	13.7 A / 13.0 A	15.2 A / 14.4 A	18.2 A / 17.3 A	19.8 A / 18.8 A	22.8 A / 21.7 A	25.8 A / 24.6 A	30.4 A / 28.9 A	
Max. output current	4.7 A	6.4 A	7.9 A	9.5 A	12.7 A	14.3 A	15.9 A	19.1 A	20.7 A	23.8 A	27 A	31.8 A	
Power factor								> 0.99 (0.8 leading - 0.8 lagging)					
THDi								< 2%					
Efficiency													
Max. efficiency			98.3%					98.5%			98.6%	98.7%	
EU efficiency			97.7%					97.9%			98.0%	98.1%	
Protection													
DC reverse-polarity protection								Yes					
Short circuit protection								Yes					
Output over current protection								Yes					
Surge protection								Yes					
Grid monitoring								Yes					
Anti-islanding protection								Yes					
Temperature protection								Yes					
Multi peak scan								Yes					
Integrated AFCI 2.0								Optional					
Integrated DC switch								Yes					
General Data													
Dimensions (W*H*D)								310 × 563 × 219 mm					
Weight	16.5 kg		16.9 kg		17.9 kg		19.6 kg		20.8 kg				
Topology								Transformerless					
Self-consumption (night)								< 1 W					
Operating ambient temperature range								-25 ~ +60°C					
Relative humidity								0 - 100%					
Ingress protection								IP66					
Noise emission (typical)					< 30 dB(A)						60 dB(A)		
Cooling concept					Natural cooling							Intelligent fan-cooling	
Max. operation altitude								4000 m					
Grid connection standard					G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1, VDE 0126/UTE C 15/VFR:2019, RD 1699/RD 244/UNE 206006/ UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530								
Safety / EMC standard					IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4								
Features													
DC connection								MC4 connector					
AC connection								Quick connection plug					
Display								LCD					
Communication								RS485, Optional: Wi-Fi, GPRS					