

## S6-EH3P(12-20)K-H

# Solis Three Phase High Voltage Energy Storage Inverters

### Features:

- Generator-compatible to extend backup duration during grid power outage
- Supports dual backup ports for intelligent control of critical and non-critical loads
- SG heat pump compatibility
- Supports a maximum input current of 20A, making it ideal for all high-power PV modules of any brand
- Supports AC voltage detection of grid and generator output to prevent damage to generators from reverse current from the grid
- Supports peak shaving features
- Supports Unbalanced and Half-Wave Loads on both the Grid and Backup Port

### Models:

S6-EH3P12K-H

S6-EH3P15K-H

S6-EH3P20K-H



# DATASHEET

## S6-EH3P(12-20)K-H

Models	12K	15K	20K
<b>Input DC (PV side)</b>			
Recommended max. PV array size	24 kW	30 kW	40 kW
Max. usable PV input power	19.2 kW	24 kW	32 kW
Max. input voltage		1000 V	
Rated voltage		600 V	
Start-up voltage		160 V	
MPPT voltage range		200 - 850 V	
Max. input current		4 × 20 A	
Max. short circuit current		4 × 30 A	
MPPT number / Max. input strings number		4 / 4	
<b>Battery</b>			
Battery type		Li-ion	
Battery voltage range		120 - 800 V	
Max. charge / discharge power	12 kW	15 kW	20 kW
Max. charge / discharge current		50 A	
Communication		CAN / RS485	
<b>Output AC (Grid side)</b>			
Rated output power	12 kW	15 kW	20 kW
Max. apparent output power	12 kVA	15 kVA	20 kVA
Rated grid voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated grid frequency		50 Hz	
Rated grid output current	18.2 A / 17.3 A	22.8 A / 21.7 A	30.4 A / 28.9 A
Max. output current	18.2 A / 17.3 A	22.8 A / 21.7 A	30.4 A / 28.9 A
Power factor		> 0.99 (0.8 leading - 0.8 lagging)	
THDi		< 3%	
<b>Input AC (Grid side)</b>			
Input voltage range		304 - 437 V / 320 - 460 V	
Max. input current	27.3 A / 26.0 A	34.2 A / 32.5 A	45.6 A / 43.3 A
Rated grid frequency		50 Hz / 60 Hz	
Frequency range		45 - 55 Hz / 55 - 65 Hz	
<b>Input Generator</b>			
Max. input power	12 kW	15 kW	20 kW
Max. input current	18.2 A / 17.3 A	22.8 A / 21.7 A	30.4 A / 28.9 A
Rated input frequency		50 Hz	
<b>Output AC (Back-up)</b>			
Rated output power	12 kW	15 kW	20 kW
Max. apparent output power	2 times of rated power, 10 s		1.6 time of rated power, 10 s
Back-up switch time		< 10 ms	
Rated output voltage		3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated frequency		50 Hz	
Rated output current	18.2 A / 17.3 A	22.8 A / 21.7 A	30.4 A / 28.9 A
THDv (@linear load)		< 3%	
<b>Efficiency</b>			
Max. efficiency		97.7%	
EU efficiency		97.5%	
BAT charged by PV max. efficiency		98.5%	
BAT charged / discharged to AC max. efficiency		97.2%	
<b>Protection</b>			
Anti-islanding protection		Yes	
Output over current protection		Yes	
Short circuit protection		Yes	
Integrated AFCI 2.0		Optional	
Integrated DC switch		Yes	
DC reverse-polarity protection		Yes	
PV over voltage protection		Yes	
Battery reverse protection		Yes	
<b>General Data</b>			
Max. allowable phase imbalance (grid & back-up)		100%	
Max. power per phase (grid & back-up)	50% rated power		40% rated power
Dimensions (W × H × D)		563 × 546 × 250 mm	
Weight		35.2 kg	
Topology		Transformerless	
Self-consumption (night)		< 25 W	
Operating ambient temperature range		-25 ~ +60°C	
Relative humidity		0 - 95%	
Ingress protection		IP66	
Noise emission (typical)		< 65 dB(A)	
Cooling concept		Intelligent fan-cooling	
Max. operation altitude		2000 m	
Grid connection standard	EN 50549-1/-10, VDE4105, CEI 0-21, CEI 0-16, NC-RFG TypeB, NRS 097-2-1, LTU-1, G99, PEA		
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4		
<b>Features</b>			
PV connection		MC4 connector	
Battery connection		OT terminal	
AC connection		OT terminal	
Display		7.0" LCD display & Bluetooth + APP	
Communication		CAN, RS485, Ethernet, Optional: Wi-Fi, Cellular, LAN	