

S6-GC(100-125)K

Solis Three Phase Grid-Tied Inverters

Efficient

- 10 MPPTs, max. efficiency 98.7%
- > 150% DC/AC ratio
- String current up to 21A, perfectly match large current bifacial modules

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life

Smart

- Supports export power control
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

Economic

- Power line communication (PLC) (optional)
- Night time PID recovery function, increases overall system yield (optional)
- DC side supports "Y" connector

Models:

S6-GC100K

S6-GC110K

S6-GC125K-HV



DATASHEET

S6-GC(100-125)K

Models	100K	110K	125K-HV
Input DC			
Max. input voltage		1100 V	
Rated voltage	600 V		720 V
Start-up voltage		180 V	
MPPT voltage range		160 - 1000 V	
Max. input current		5 × (42 A / 36 A)	
Max. short circuit current		10 × 50 A	
MPPT number / Max. input strings number		10 / 20	
Output AC			
Rated output power	100 kW	110 kW	125kW
Max. apparent output power	110 kVA	121 kVA	137.5 kVA
Max. output power	110 kW	121 kW	137.5 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V		3/PE, 480 V
Rated grid frequency		50 Hz / 60 Hz	
Rated grid output current	152.0 A / 144.3 A	167.1 A / 158.8 A	150.4 A
Max. output current	167.1 A	183.8 A	165.4 A
Power factor		> 0.99 (0.8 leading - 0.8 lagging)	
THDi		< 3%	
DC injection current		0.5%In	
Efficiency			
Max. efficiency		98.7%	
EU efficiency		98.3%	
Protection			
DC reverse-polarity protection		Yes	
Short circuit protection		Yes	
Output over current protection		Yes	
Insulation resistance monitoring		Yes	
Residual current detection		Yes	
Surge protection		DC Type II / AC Type II	
Grid monitoring		Yes	
Anti-islanding protection		Yes	
Temperature protection		Yes	
Strings monitoring		Yes	
I/V Curve scanning		Yes	
Integrated AFCI 2.0		Optional	
Integrated PID recovery		Optional	
Integrated DC switch		Yes	
Integrated AC switch		Optional	
General Data			
Dimensions (W*H*D)		1014 × 567 × 345 mm	
Weight		96 kg	
Topology		Transformerless	
Self-consumption (night)		< 2 W	
Operating ambient temperature range		- 30 ~ +60°C	
Relative humidity		0 - 100%	
Ingress protection		IP66	
Noise emission (typical)		< 80dB(A)	
Cooling concept		Intelligent fan-cooling	
Max. operation altitude		4000 m	
Grid connection standard	G99, IEC61727, EN50549-1/2, VDE4110		NB/T 32004
Safety / EMC standard		IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4	
Features			
DC connection		MC4 connector	
AC connection		OT terminal (max. 240 mm ²)	
Display		LCD	
Communication		RS485, Optional: S3-WiFi-ST, S3-GRPS-ST, PLC	