

## S6-GC(100-125)K

# Solis Three Phase Grid-Tied Inverters

### Efficient

- 10 MPPTs, max. efficiency 98.7%
- > 150% DC/AC ratio
- String current up to 21A, perfectly match large current bifacial modules

### Smart

- Supports export power control
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

### Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life

### Economic

- Power line communication (PLC) (optional)
- Night time PID recovery function, increases overall system yield (optional)
- DC side supports "Y" connector

### Models:

- S6-GC100K
- S6-GC110K
- S6-GC125K
- S6-GC125K-HV



## DATASHEET

## S6-GC(100-125)K

Models	100K	110K	125K	125K-HV
<b>Input DC</b>				
Max. input voltage	1100 V			
Rated voltage	600 V			720 V
Start-up voltage	180 V			
MPPT voltage range	160 - 1000 V			
Max. input current	5 × (42 A / 36 A)			
Max. short circuit current	10 × 50 A			
MPPT number / Max. input strings number	10 / 20			
<b>Output AC</b>				
Rated output power	100 kW	110 kW	125 kW	125kW
Max. apparent output power	110 kVA	121 kVA	125 kVA	137.5 kVA
Max. output power	110 kW	121 kW	125 kW	137.5 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V			3/PE, 480 V
Rated grid frequency	50 Hz / 60 Hz			
Rated grid output current	152.0 A / 144.3 A	167.1 A / 158.8 A	189.9 A / 180.4 A	150.4 A
Max. output current	167.1 A	183.8 A	189.9 A	165.4 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)			
THDi	< 3%			
<b>Efficiency</b>				
Max. efficiency	98.7%			
EU efficiency	98.3%			
<b>Protection</b>				
DC reverse-polarity protection	Yes			
Short circuit protection	Yes			
Output over current protection	Yes			
Surge protection	DC Type II / AC Type II			
Grid monitoring	Yes			
Anti-islanding protection	Yes			
Temperature protection	Yes			
Strings monitoring	Yes			
I/V Curve scanning	Yes			
Integrated AFCI 2.0	Optional			
Integrated PID recovery	Optional			
Integrated DC switch	Yes			
Integrated AC switch	Optional			
<b>General Data</b>				
Dimensions (W × H × D)	1014 × 567 × 345 mm			
Weight	96 kg			
Topology	Transformerless			
Self-consumption (night)	< 2 W			
Operating ambient temperature range	-30 ~ + 60°C			
Relative humidity	0 - 100%			
Ingress protection	IP66			
Cooling concept	Intelligent fan-cooling			
Max. operation altitude	4000 m			
Grid connection standard	G99, IEC61727, EN50549-1/2, VDE4110			IEC61727
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4			
<b>Features</b>				
DC connection	MC4 connector			
AC connection	OT terminal (max. 240 mm <sup>2</sup> )			
Display	LCD			
Communication	RS485, Optional: Wi-Fi, GPRS, PLC			