

S6-GC3P(25-36)K03-NV-ND

Solis Three Phase Grid-Tied Inverters

Features:

- Max. efficiency 98.5%
- String current up to 20A
- > 150% DC/AC ratio, supports high power modules
- Automatic voltage stabilization technology in weak grid conditions
- AFCI protection, proactively reduces fire risk
- Supports RS485/ WiFi/GPRS/4G
- Scan to register on SolisCloud, supports remote upgrade and control



Models:

S6-GC3P25K03-NV-ND
S6-GC3P30K03-NV-ND
S6-GC3P33K03-NV-ND
S6-GC3P36K03-NV-ND

DATASHEET

S6-GC3P(25-36)K03-NV-ND

Models	25K	30K	33K	36K
Input DC				
Recommended max. PV power	37.5 kW	45 kW	49.5 kW	54 kW
Max. input voltage			1100 V	
Rated voltage			600 V	
Start-up voltage			180 V	
MPPT voltage range			180 - 1000 V	
Max. input current			40 A / 40 A / 40 A	
Max. short circuit current			50 A / 50 A / 50 A	
MPPT number / Max. input strings number			3 / 6	
Output AC				
Rated output power	25 kW	30 kW	33 kW	36 kW
Max. apparent output power	25 kVA	30 kVA	33 kVA	36 kVA
Max. output power	25 kW	30 kW	33 kW	36 kW
Rated grid voltage			3/N/PE, 220 V / 380 V, 230 V / 400 V	
Rated grid frequency			50 Hz	
Rated grid output current	38.0 A / 36.1 A	45.6 A / 43.3 A	50.1 A / 47.6 A	54.7 A / 52 A
Max. output current	38.0 A / 36.1 A	45.6 A / 43.3 A	50.1 A / 47.6 A	54.7 A / 52 A
Power factor			> 0.99 (0.8 leading - 0.8 lagging)	
THDi			< 3%	
Efficiency				
Max. efficiency			98.5%	
EU efficiency			98%	
Protection				
DC reverse-polarity protection			Yes	
Short circuit protection			Yes	
Output over current protection			Yes	
Surge protection			DC Type II / AC Type II	
Grid monitoring			Yes	
Anti-islanding protection			Yes	
Temperature protection			Yes	
Strings monitoring			Yes	
I/V Curve scanning			Yes	
Multi peak scan			Yes	
Integrated AFCI 2.0			Optional	
Integrated DC switch			Yes	
General Data				
Dimensions (W × H × D)			355 × 625 × 250 mm	
Weight	25.3 kg	25.5 kg	26.5 kg	
Topology			Transformerless	
Self-consumption (night)			< 1 W	
Operating ambient temperature range			-25 ~ +60°C	
Relative humidity			0 - 100%	
Ingress protection			IP66	
Noise emission (typical)			≤ 60 dB(A)	
Cooling concept			Intelligent fan-cooling	
Max. operation altitude			4000 m	
Grid connection standard	G98 or G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1, VDE 0126/UTE C 15/VFR:2019, RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC60068, IEC 61683, EN 50530			
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4			
Features				
DC connection			MC4 connector	
AC connection			OT terminal	
Display			LED digital display & Bluetooth + APP	
Communication			RS485, Optional: Wi-Fi, GPRS	