

S6-GR1P(2.5-6)K-S

Solis Single Phase Inverters

>> Models:

S6-GR1P2.5K-S	S6-GR1P4.6K-S
S6-GR1P3K-S	S6-GR1P5K-S
S6-GR1P3.6K-S	S6-GR1P6K-S
S6-GR1P4K-S	



Features:

- String current up to 16A
- Integrated with zero export power control function
- Light weight with compact design for easy installation
- 2 MPPT design with precise MPPT algorithm

DATASHEET**S6-GR1P(2.5-6)K-S**

Models	2.5K	3K	3.6K	4K	4.6K	5K	6K
Input DC							
Recommended max. PV power	3.75 kW	4.5 kW	5.4 kW	6 kW	6.9 kW	7.5 kW	9 kW
Max. input voltage				550 V			
Rated voltage	250 V			330 V			
Start-up voltage	60 V			100 V			
MPPT voltage range	50-550 V			90-550 V			
Max. input current				16 A / 16 A			
Max. short circuit current				22 A / 22 A			
MPPT number/Max. input strings number				2/2			
Output AC							
Rated output power	2.5 kW	3 kW	3.6 kW	4 kW	4.6 kW	5 kW	6 kW
Max. apparent output power	2.5 kVA	3 kVA	3.6 kVA	4 kVA	4.6 kVA	5 kVA	6 kVA
Max. output power	2.5 kW	3 kW	3.6 kW	4 kW	4.6 kW	5 kW	6 kW
Rated grid voltage				1/N/PE, 220 V / 230 V			
Rated grid frequency				50 Hz / 60 Hz			
Rated grid output current	11.4 A / 10.9 A	13.6 A / 13 A	16 A / 15.7 A	18.2 A / 17.4 A	20.9 A / 20 A	22.7 A / 21.7 A	27.3 A / 26.1 A
Max. output current	11.4 A	13.6 A	16 A	18.2 A	20.9 A	22.7 A	27.3 A
Power factor				>0.99 (0.8 leading - 0.8 lagging)			
THDi				<3%			
DC injection current				<0.5% In			
Efficiency							
Max. efficiency	97.3%	97.3%	97.3%	97.6%	97.6%	97.7%	97.7%
EU efficiency	96.5%	96.6%	96.6%	97.1%	97.1%	97.1%	97.1%
Protection							
DC reverse-polarity protection				Yes			
Short circuit protection				Yes			
Output over current protection				Yes			
Surge protection				Yes			
Grid monitoring				Yes			
Anti-islanding protection				Yes			
Temperature protection				Yes			
Integrated AFCI (DC arc-fault circuit protection)				Yes ⁽¹⁾			
Integrated DC switch				Yes			
General Data							
Dimensions (W*H*D)				330*371*161 mm			
Weight		8.2 kg			9 kg		
Topology				Transformerless			
Self-consumption (night)				<1 W			
Operating ambient temperature range				-25 ~ +60°C			
Relative humidity				0-100%			
Ingress protection				IP66			
Noise emission (typical)				<20 dB(A)			
Cooling concept				Natural convection			
Max. operation altitude				4000 m			
Grid connection standard		IEC 61683, IEC 60068, IEC 61727, IEC 62116, EN 50530, IS 16169 / IS 16221(BIS)					
Safety/EMC standard				IEC 62109-1-2, IEC 61000-6-2/-3			
Features							
DC connection				MC4 connector			
AC connection				Quick connection plug			
Display				LED + APP			
Communication				RS485, USB, Optional: Wi-Fi, GPRS			

(1) Activation required.