

Solis-(215-255)K-EHV-5G

Solis Three Phase Grid-Tied Inverters

Efficient

- 9/12/14 MPPTs, max. efficiency 99.0%
- > 150% DC/AC ratio
- High power tracking density 56MPPT/MW
- Compatible with 550W+ bifacial modules

Safe

- IP66
- Built-in PID recovery for better module performance
- Fuse free design, safe and maintenance free
- Globally recognised branded componentry for longer life

Smart

- Night SVG function
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector

Models:

Solis-215K-EHV-5G-PLUS

Solis-250K-EHV-5G

Solis-250K-EHV-5G-PLUS

Solis-255K-EHV-5G

Solis-255K-EHV-5G-PLUS



360° View



DATASHEET

Solis-(215-255)K-EHV-5G

| Models | 215K-PLUS | 250K | 250K-PLUS | 255K | 255K-PLUS |
|---|-----------|-----------|--|-----------|-----------|
| Input DC | | | | | |
| Max. input voltage | | | 1500 V | | |
| Rated voltage | | | 1080 V | | |
| Start-up voltage | | | 500 V | | |
| MPPT voltage range | | | 480 - 1500 V | | |
| Max. input current | 9 × 30 A | 14 × 26 A | 12 × 30 A | 14 × 26 A | 12 × 30 A |
| Max. short circuit current | 9 × 50 A | 14 × 40 A | 12 × 50 A | 14 × 40 A | 12 × 50 A |
| MPPT number / Max. input strings number | 9 / 18 | 14 / 28 | 12 / 24 | 14 / 28 | 12 / 24 |
| Output AC | | | | | |
| Output power | 215 kVA | | 250 kVA | | 255 kVA |
| Rated grid voltage | | | 3/PE, 800 V | | |
| Grid voltage range | | | 640 - 920 V | | |
| Rated grid frequency | | | 50 Hz / 60 Hz | | |
| Max. output current | 155.2 A | | 180.4 A | | 184.0 A |
| Power factor | | | > 0.99 (0.8 leading - 0.8 lagging) | | |
| THDi | | | < 3% | | |
| DC injection current | | | < 0.5% In | | |
| Efficiency | | | | | |
| Max. efficiency | | | 99.0% | | |
| EU efficiency | 98.8% | 98.7% | 98.8% | 98.7% | 98.8% |
| Protection | | | | | |
| DC reverse-polarity protection | | | Yes | | |
| Short circuit protection | | | Yes | | |
| Output over current protection | | | Yes | | |
| Insulation resistance monitoring | | | Yes | | |
| Residual current detection | | | Yes | | |
| Surge protection | | | DC Type II / AC Type II | | |
| Grid monitoring | | | Yes | | |
| Anti-islanding protection | | | Yes | | |
| Temperature protection | | | Yes | | |
| Strings monitoring | | | Yes | | |
| I/V Curve scanning | | | Yes | | |
| Night time SVG function | | | Yes | | |
| Integrated PID recovery | | | Yes | | |
| Integrated DC switch | | | Yes | | |
| General Data | | | | | |
| Dimensions (W*H*D) | | | 1125 × 770 × 384 mm | | |
| Weight | 109 kg | | 113 kg | | |
| Topology | | | Transformerless | | |
| Self-consumption (night) | | | < 2 W | | |
| Operating ambient temperature range | | | - 30 ~ +60°C | | |
| Relative humidity | | | 0 - 100% | | |
| Ingress protection | | | IP66 | | |
| Noise emission (typical) | | | ≤ 80 dB(A) | | |
| Cooling concept | | | Intelligent fan-cooling | | |
| Max. operation altitude | | | 4000 m | | |
| Grid connection standard | | | EN50549, G99, AS4777.2, VDE0126, IEC61727, VDE4110, CEA 2019 | | |
| Safety / EMC standard | | | IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4 | | |
| Features | | | | | |
| DC connection | | | MC4 connector | | |
| AC connection | | | OT terminal (max. 300 mm ²) | | |
| Display | | | LCD | | |
| Communication | | | RS485, Optional: PLC | | |